LITERATURE UPDATE

These product bulletins, brochures and catalogs are free. To order copies, goto www.SandVinfo.com, select the July issue and enter RS numbers of interest.

World's First Multifield Microphone



the launch of the world's first multifield measuring microphone. Type 4961 is a unique 1/4-inch measuring microphone with the same low noise floor as a 1/2-inch microphone, and optimized multifield response. Tel: 800-332-2040 www.bksv.com

Brüel & Kjær announces

RS #221 Brüel & Kjær


Dynamic Signal Analyzer



2/4/8/16 inputs and one signal source. Sample all inputs up to 102.4 kHz. 130-dB dynamic range. Continuous recording at full speed. FFT sizes up to 64 K. FRF, tri-spectra, octave, order tracking. Weight <1.7 kg. Battery life >6 hours. 5.7" color LCD. Ethernet, USB. SD card and wireless. Contact: 408.986.8880. www.go-ci.com

RS #222 **Crystal Instruments**

Vibration Isolation Elastomers



Getzner Werkstoffe has developed a wide range of materials for vibration isolation. Sylomer has an impressive track record, and has been used throughout Europe. Soundown Corporation is now supplying OEM and architectural applications in North America. Contact: 800.359.1036 or www.soundown.com

BS #223 Soundown Corporation

The Latest in Vibration Control



Vibration Research designs and manufactures innovative vibration control systems for electro-dynamic and servohydraulic shakers. Our team brings together experience in vibration testing, hard/ software development, and has a strong desire to take vibration testing to a new level. www.vibration research.com/about movie.

Vibration Research Corp.

Noise Control Panels



Eckel's high-performance acoustic wall and ceiling panel systems efficiently and economically reduce background noise and reverberation in interior spaces. They are durable, low maintenance, attractive and simple to install. Ideal for renovation programs and for new construction projects.

RS #225


Eckel Industries, Inc., Acoustic Division

Thinner, Faster, Quieter Floors



New Acousti-Mat® LP (Low Profile) or LPR (LP with Reinforcement) is the thinner, faster way to quiet floors. Floor goods can be glued directly to the <1/16-inchthick Acousti-Mat LP in concrete, wood, or steel-frame construction. The low profile 3/4-inch Acousti-Mat LPR system is ideal for apartment construction. www.amlowprofile.com

RS #226 Maxxon Corp.



RS #227

MIMO Control from Spectral Dynamics For Multi-Shaker testing,



The guide presents The

Modal Shop's shaker family

highlighted by the Smart-

Shaker[™] with integrated

Spectral Dynamics, Inc.

Electrodynamic Exciter Selection Guide



RS #228

power amplifier. Specifications are listed for the mini, through-hole modal and dual-purpose platform exciters. Graphical layout and kit configurations simplify selection process, insuring all necessary shaker, amplifier, stingers, blowers and accessories are included. The Modal Shop

Introducing PULSE Reflex

The Product of Intuition

PULSE REFLEX" Designed in close cooperation with end-users from diverse sectors of industry across the world, PULSE Reflex has ease of use and high-productivity concepts at its core. PULSE Reflex gives you: Intuitive user interface, powerful data management and enhanced reporting opportunities. Tel: 800-332-2040 www.bksv.com

RS #229 Brüel & Kjær



ARMD bv RBTS **RS #230 RBTS**, Inc.

Advanced Rotating Machinery Dynamics (ARMD) software has been proven effective by companies worldwide. The most advanced software for bearings, rotor dynamics and torsional vibration. ARMD features user-friendly help. graphics and much more.

Tel: 610.415.0412 FAX: 610.415.0413 www.rbts.com

BSWA Microphones



BSWA has more than 20 years of experience in producing measurement microphones. Each year we supply thousands of microphones to OEMs. We have a wide range of models to fit your application needs.

Tel: +86.10.5128.5118 www.bswa-tech.com

RS #231 BSWA Technology Co., Ltd.

Low-Cost Vibration Test Systems



100 lbf system \$6466, complete with vibrator, base, blower, linear low-distortion amplifier, all cables and hoses. Low-cost digital controller converts PCs to powerful vibration controllers. Low as \$3995 for sine. \$7990 for new complete 4-channel control package.

Vibration Test Systems

Modal Analysis with ME'scopeVES 5.0



ME'scopeVES 5.0 contains all of the tools to visualize. analyze and document noise & vibration problems in structures and machinery. A variety of ODS, Modal, and Operating Modal techniques are available, as well as advanced SDM and FEA Model Updating tools.

www.vibetech.com

RS #233 Vibrant Technology, Inc.

Noise Control Products and Systems



RS #234

IAC offers a comprehensive line of sound control products. IAC is unique in guaranteeing product performance; prior to shipment, each product line is pre-tested for performance in our in-house Aero-Acoustic Research Lab. IAC always guarantees in-field performance to the specification. www.industrialacoustics com

Industrial Acoustics Company, Inc.

Excellent Vibration Damping



Environmentally friendly and stable in extreme temperatures, silicone gel shock-absorbing and vibration-damping products; a superior alternative to traditional materials. Their unique ability to absorb and disperse energy is due to the softness of the silicone gel. Tel: 516.328.3662 www.vibrationmounts.com

RS #235 Advanced Antivibration Components

High Temperature Accelerometers



BS #236

Dytran's new brochure focuses on IEPE and chargemode accelerometers for high-temperature applications. Dytran has over 30 years of experience in the successful design and manufacture of high-temperature piezoelectric sensing technologies. For assistance in evaluating your application requirements, e-mail Dytran at info@dvtran.com.

Dytran Instruments, Inc.

New 2010 Measurement Product Resource



Meggitt Sensing Systems released its 2010 Measurement Product Resource, a catalog, highlighting select models of high-reliability Endevco, Sensorex, Vibro-Meter and Wilcoxon Research sensing technologies for aerospace, automotive, industrial, R&D and test and measurement markets. Download a free copy from www.endevco.com.

RS #237 **Meggitt Sensing Systems**

Material Solutions for Peace and Quiet



Soundown has expanded its materials product line to cover growing customer needs. The approach to product design, selection, and manufacturing is based on professional engineering, understanding NVH science and practical experience with materials. Contact: 800.359.1036 or www.so<u>undown.com</u>

RS #238 Soundown Corporation

LAN-XI Acquisition Hardware



RS #239

Imagine using the same equipment to make a multichannel measurement using several large rack systems one day, and a simpler twochannel measurement using a single module the next. With LAN-XI this is reality. One system does it all

Tel: 800-332-2040 www.bksv.com

Brüel & Kjær

Environmental Noise in Full Color



The CEL-630 is data logging sound level analyzer with full-color and high-resolution LCD, large memory and ease of use. It's not necessary to choose what to measure – CEL-630 measures everything on a wide single range. Collect noise data in periods and short time history profiles . www.casellausa.com

RS #240 Casella USA

Portable Anechoic Chambers (PACs)



Eckel offers preassembled, sectional and modular styles of high-performance PACs in many sizes for noise equipment; microphone calitesting of loudspeakers; and

Eckel Industries, Inc., Acoustic Division

LMS Test.Lab Solution Guide



Designed to make testing more efficient, LMS Test. Lab and the LMS SCADAS data acquisition systems are the solutions that testing departments count on to increase test productivity, maintain quality and achieve a higher return on investment from existing test facilities. Guide presents packaged solutions. www.lmsintl.com

RS #242 LMS North America

Dynamic Data Recorders



RS #243

features selectable 24/16bit resolution and uses any capacity flash-memory cards. DC, IEPE and strain input, analog and digital output, LAN-Ethernet interface, and multi-unit record sync. LX also functions as front-end for direct PC HDD recording. Contact: 978.468.4135 or systems.com

TEAC I X-100 series

Tritek / TEAC Data Recorders

3-Inch-Stroke H-Series Shakers



We now offer a choice of armature sizes for all 3-inchstroke H-Series Shaker Systems. Available with either 17.5- or 25.75-inch diameter armature, these systems are rated from 7,200 - 8,000 lbf. Each has 3 inches of stroke, 100% air-cooled, and configurable with low-profile, pedestal or horizontal slip table base. www.udco.com

RS #244 Unholtz-Dickie Corp.

Four-Channel Touch-Screen Analyzer



Enjoy 40-kHz BW real time on four channels. FRF, coherence displays at the same time, 8+ battery life, USB, compact flash card. 1/3 octave, order tracking, balancing, continuous recording, bearing analysis and more. Free lifetime firmware updates with purchase.

RS #245 Benstone

Tel: 651.257.6500 www.benstone.com

Endevco Acoustic Sensor Selection Guide



Meggitt Sensing Systems, has released its new Endevco microphones and preamplifiers selection guide highlighting Meggitt's extensive range of precision acoustic sensors and instrumentation for automotive NVH, cabin noise, vibroacoustic testing, appliance noise evaluation, wind tunnel testing and other critical applications.

RS #246 **Meggitt Sensing Systems**

Sound-Retardant Products



All Overly acoustical products have been independently tested to ASTM standards. In addition, Overly has successfully tested many of its acoustical products to UL fire test standards, including UL 10B (neutral pressure) and UL10C/UBC 7-2 (positive pressure). Tel: 800.979.7300

Overly Door Company

Properties of Acoustical Materials



Spectronics' ACUPRO system takes the guesswork out of using sound-absorbing materials. Make your own measurement of sound absorption or transmission loss; don't rely on suppliers' data any longer. Use your DAQ system or one we supply. Tel: 859-321-1843

www.spectronics.net

Spectronics, Inc.

research. Available with low-frequency cutoffs from 150-500 Hz.

studies of small electronic, electrical and mechanical bration; free-field response other acoustic testing and

RS #241